

## **Surface Water Drainage Strategy**




Land at Llanellen Court, Llanellen, Monmouthshire

On Behalf of

Trustees of Morspan Pension Scheme Ltd

---

## Quality Management

|                                    |                                                                                                                                                                                                                       |                                                                                     |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <b>Prepared by:</b>                | Tom Paltridge<br>BSc MSc FGS                                                                                                                                                                                          |  |
| <b>Reviewed and Authorised by:</b> | Chris Betts<br>BSc MSc CGeol FGS                                                                                                                                                                                      |  |
| <b>Calculations Approved by:</b>   | Chris Betts<br>BSc MSc CGeol FGS                                                                                                                                                                                      |  |
| <b>Date:</b>                       | December 2023                                                                                                                                                                                                         |                                                                                     |
| <b>Version:</b>                    | 1                                                                                                                                                                                                                     |                                                                                     |
| <b>Project Number:</b>             | HYG953                                                                                                                                                                                                                |                                                                                     |
| <b>Document Reference:</b>         | HYG953 R 231207 TP Llanellen SuDS Strategy                                                                                                                                                                            |                                                                                     |
| <b>Document File Path:</b>         | https://hydrogeoltd-my.sharepoint.com/personal/mike_hydrogeo_co_uk/Documents/Projects/HYG953 P Llanellen & Prioress Mill Lane Lane/Reports/Llanellen North Site/Final/HYG953 R 231207 TP Llanellen SuDS Strategy.docx |                                                                                     |

### COPYRIGHT © Hydrogeo

This report has been produced by Hydrogeo within the terms of the contract with the client and taking account of the resources devoted to it by agreement with the client.

We disclaim any responsibility to the client and others in respect of any matters outside the scope of the above.

This report is confidential to the client and we accept no responsibility of whatsoever nature to third parties to whom this report, or any part thereof, is made known. Any such party relies on the report at their own risk.



Hydrogeo Ltd,  
Unit 4 Waddington House,  
Llanover Business Centre, Llanover,  
Monmouthshire NP7 5NT  
T: 01873 856813  
E: [chris@hydrogeo.co.uk](mailto:chris@hydrogeo.co.uk)  
W: [www.hydrogeo.co.uk](http://www.hydrogeo.co.uk)

# Contents

---

|                                                            |           |
|------------------------------------------------------------|-----------|
| <b>Quality Management.....</b>                             | <b>i</b>  |
| <b>Contents .....</b>                                      | <b>ii</b> |
| <b>1 Introduction .....</b>                                | <b>7</b>  |
| 1.1 Background.....                                        | 7         |
| 1.2 Surface Water Discharge Planning Requirements .....    | 7         |
| <b>2 Location &amp; Development Description.....</b>       | <b>8</b>  |
| 2.1 Site Location .....                                    | 8         |
| 2.2 Existing Development .....                             | 9         |
| 2.3 Potential Development .....                            | 9         |
| 2.4 Geology .....                                          | 10        |
| 2.5 Hydrogeology .....                                     | 10        |
| 2.6 Catchment Hydrology.....                               | 11        |
| 2.7 Flooding .....                                         | 12        |
| 2.8 Sensitive Land Uses .....                              | 12        |
| 2.9 Sewers.....                                            | 12        |
| <b>3 Site Walkover.....</b>                                | <b>13</b> |
| 3.1 Introduction.....                                      | 13        |
| <b>4 Surface Water Drainage.....</b>                       | <b>15</b> |
| 4.1 Introduction.....                                      | 15        |
| <b>5 S1: Surface Water Run-Off Destination.....</b>        | <b>16</b> |
| 5.1 Introduction.....                                      | 16        |
| 5.2 Collect for re-use .....                               | 16        |
| 5.3 Infiltrate to ground.....                              | 16        |
| 5.4 Discharge to a surface water body.....                 | 16        |
| 5.5 Discharge to sewers .....                              | 17        |
| <b>6 S2: Surface Water Run-Off Hydraulic Control .....</b> | <b>18</b> |

|                                                                                                        |           |
|--------------------------------------------------------------------------------------------------------|-----------|
| <b>6.1 Introduction.....</b>                                                                           | <b>18</b> |
| <b>6.2 Site Areas .....</b>                                                                            | <b>18</b> |
| <b>6.3 Surface Water Run-Off Rates.....</b>                                                            | <b>19</b> |
| <b>6.4 Surface Water Attenuation Estimation.....</b>                                                   | <b>19</b> |
| <b>6.5 Drainage Strategy .....</b>                                                                     | <b>20</b> |
| <b>6.6 Interception .....</b>                                                                          | <b>20</b> |
| <b>6.7 Designing for Local Drainage System Failure/Design Exceedance .....</b>                         | <b>20</b> |
| <b>7 S3: Water Quality .....</b>                                                                       | <b>22</b> |
| <b>8 S4 &amp; S5: Amenity and Biodiversity.....</b>                                                    | <b>24</b> |
| <b>8.1 Amenity and Biodiversity Benefits .....</b>                                                     | <b>24</b> |
| <b>9 S6: Designing Drainage for Construction, Operation, Maintenance and Structural Integrity.....</b> | <b>25</b> |
| <b>9.1 Introduction.....</b>                                                                           | <b>25</b> |
| <b>9.2 SuDS Maintenance and Management.....</b>                                                        | <b>25</b> |
| <b>9.3 Design Life .....</b>                                                                           | <b>25</b> |
| <b>10 Conclusion .....</b>                                                                             | <b>26</b> |
| <b>10.1 Introduction.....</b>                                                                          | <b>26</b> |
| <b>10.2 Surface Water Drainage .....</b>                                                               | <b>26</b> |

## Tables and Figures

---

### Tables

|                                                                        |           |
|------------------------------------------------------------------------|-----------|
| <i>Table 3-1 Site walkover photographs .....</i>                       | <i>13</i> |
| <i>Table 6-1 – Site features and surfaces. ....</i>                    | <i>19</i> |
| <i>Table 7-1 - Potential pollution source and hazard indices. ....</i> | <i>22</i> |
| <i>Table 7-2 – Mitigation indices for SuDS components. ....</i>        | <i>23</i> |

### Figures

|                                       |          |
|---------------------------------------|----------|
| <i>Figure 2-1 Site Location .....</i> | <i>8</i> |
| <i>Figure 2-2 Site boundary .....</i> | <i>9</i> |

## Drawings

---

|                         |                                           |
|-------------------------|-------------------------------------------|
| <b><i>Drawing 1</i></b> | <b><i>Surface water features plan</i></b> |
| <b><i>Drawing 2</i></b> | <b><i>Flooding hazard plan</i></b>        |
| <b><i>Drawing 3</i></b> | <b><i>Photo location plan</i></b>         |
| <b><i>Drawing 4</i></b> | <b><i>Surface Water Drainage Plan</i></b> |

## Appendices

---

|                          |                                                               |
|--------------------------|---------------------------------------------------------------|
| <b><i>Appendix A</i></b> | <b><i>Proposed site layout plan</i></b>                       |
| <b><i>Appendix B</i></b> | <b><i>DCWW sewer plan</i></b>                                 |
| <b><i>Appendix C</i></b> | <b><i>Causeway Flow Calculations</i></b>                      |
| <b><i>Appendix D</i></b> | <b><i>Drainage Survey and Topographic Survey</i></b>          |
| <b><i>Appendix E</i></b> | <b><i>Llanellen Access Road Drainage Statement (2017)</i></b> |

# 1 Introduction

---

## 1.1 Background

Hydrogeo Limited (Hydrogeo) have been commissioned by the Trustees of Morspan Pension Scheme Ltd (the Client) to undertake a Surface Water Drainage Strategy Report for a parcel of land at Llanellen Court, Llanellen, Monmouthshire (the Site).

This report has been prepared to promote the Site for inclusion in the Monmouthshire County Council (MCC) Local Development Plan (LDP) for residential land use. In order for the Site to be subject to a successful future planning application the surface water discharges would need to meet current planning requirements.

## 1.2 Surface Water Discharge Planning Requirements

A development of more than 100 square metres would need a Sustainable Drainage System (SuDS) designed, submitted to and approved by the Monmouthshire Council SuDS Approving Body (SAB) in order to gain full planning approval.

A Sustainable Drainage System is designed to replicate, as closely as possible, the natural drainage from a site (before development) to ensure that the flood risk downstream of that site does not increase as a result of the land being developed.

SuDS can also significantly improve the quality of water leaving a site and can enhance the amenity and biodiversity that a site has to offer.

The implications of the SuDS requirements for development at the Site are a key focus of this report, and are discussed in greater detail in Section 4, with discussion of the site-specific options included in Section 6.

## 2 Location & Development Description

### 2.1 Site Location

The Site is located on land off the A4042 at Llanellen Court, Llanellen, Monmouthshire, NP7 9HP. The National Grid Reference for the Site is 330317, 210655.

The location of the Site has been shown in Figure 2-1 and the Site boundary has been shown in Figure 2-2.

**Figure 2-1 Site Location**



© Crown copyright reserved, Licence No. 100047852

**Figure 2-2 Site boundary**

© Microsoft 2021

## 2.2 Existing Development

The Site comprises an undeveloped parcel of land at Llanellen Court, as shown in Figure 2-2. The parcel of land has an area of approximately 3.5ha and is currently used for pasture.

The land falls towards the north east with a break in slope halfway to a level area at the northern half. The maximum elevation is approximately 64m above ordnance datum (mAOD) along the south west boundary, and the minimum elevation is approximately 53mAOD across the flat northern part.

The land falls within a wider ownership boundary which includes a number of former farming buildings, residential buildings and dwellings.

## 2.3 Potential Development

The land at the Site is a LDP candidate sites for MCC, with a proposed residential end use. Planning permission for development at the Site has not been sought yet.

The development layout plan for the site is attached at Appendix A.

## 2.4 Geology

British Geological Survey (BGS) data have been used to describe the geology below the Site.

### Artificial Geology

No artificial geology is indicated to be present below the Site on BGS mapping.

### Superficial Geology

Superficial deposits are present at the Site and comprise mainly Glaciofluvial Sheet Deposits. These are sand and gravel deposits formed by glacial processes during the Quaternary Period within the last 2 million years.

Superficial deposits at the flat northern part of the northern parcel of land are marked as Alluvium: clay, silt, sand and gravel deposited in a fluvial environment during the Quaternary Period within the last 2 million years.

### Bedrock Geology

BGS mapping indicates that the bedrock geology present at the Site comprises the St. Maughans Formation, which consists of fluvially derived interbedded sandstone and argillaceous rocks dating from the Devonian Period, approximately 393 to 419 million years ago.

## 2.5 Hydrogeology

The following aquifer classifications have been assigned by NRW to the superficial and bedrock geology below the Site:

- Groundwater vulnerability, superficial geology: *Medium vulnerability, secondary aquifer.*
- Groundwater vulnerability, bedrock geology: *Medium vulnerability, secondary aquifer.*
- Aquifer designation, superficial geology: Secondary A.
- Aquifer designation, bedrock geology: Secondary A.

Secondary A Aquifers are permeable layers capable of supporting water supplies at a local rather than strategic scale, and in some cases forming an important source of base flow to rivers.

### **Soil Type**

Information from the National Soil Resource Institute identifies the Site as being situated on Soilscape 6: freely draining slightly acid loamy soils.

## **2.6 Catchment Hydrology**

Available Ordnance Survey (OS) mapping has been used to determine the surface water features in the vicinity of the Ownership Site. (Drawing 1)

A site walkover was conducted by Hydrogeo on the 30th July 2021 in order to identify surface water features and gain an understanding of the general site layout relative to site drainage. The site walkover is discussed in Section 3.

No surface water features are present directly within the boundary of the Site. OS mapping indicates that a spring is present 210m south west of the northern parcel of land. The spring feeds a small pond to the west of residential buildings within the site ownership boundary; the pond outfall is then culverted below an area of woodland down slope to the north east, in the direction of the Site.

The culverted watercourse has been surveyed by CCTV and dye tracing by PM Consultants (Appendix D)

The culvert is concrete and starts at a diameter of 225mm, then increases to 300mm after MH1 where the private surface water sewer from Llanellen Village joins. The culvert leaves the land ownership in the north and it is understood that there is another access manhole on the field to the north east. The OS map shows a short section of open watercourse in the north of the field (Drawing 1), which then passes beneath the B4269 and the A4042 prior to another open section which discharges to the River Usk south of the road bridge. It is assumed that this is the route of the culverted watercourse, which can be surveyed further and cleaned / reinstated where required by the landowners under Riparian Rights.

A plan of the surface water features in the vicinity of the Site has been shown on Drawing 1.

## 2.7 Flooding

NRW data have been used to summarise the flood hazards at the Site. A plan of the flooding hazards has been shown on Drawing 2.

### Flooding from Rivers and Sea

- The Site is not at risk of flooding from the sea.
- The Site is not at risk of flooding from rivers.

### Flooding from Surface Water and Small Watercourses

- The Site is not at risk of flooding from small watercourses.
- A small area at the north eastern corner of the northern parcel of land at the Site is at high risk of surface water flooding.
- A small strip of land at the south western corner of the southern parcel of land at the Site is at low risk of surface water flooding.

## 2.8 Sensitive Land Uses

NRW data has been used to determine whether any sensitive land uses are present in the vicinity of the Site.

A list of sensitive land uses has been shown below:

- |                         |                                        |
|-------------------------|----------------------------------------|
| ▪ SSSI:                 | River Usk (Lower Usk) located 0.3km NE |
| ▪ SAC:                  | River Usk located 0.3km NE             |
| ▪ AONB:                 | None within 2km                        |
| ▪ Local Nature Reserve: | None within 2km                        |
| ▪ National Park:        | Brecon Beacons NP located 0.3km W      |
| ▪ RAMSAR:               | None within 2km                        |

## 2.9 Sewers

Sewer plans have been requested from Dŵr Cymru Welsh Water (DCWW); the sewer plan and DCWW correspondence has been attached at Appendix B. A private sewer from Llanellen village discharges to the culverted watercourse which crosses the site.

### 3 Site Walkover

#### 3.1 Introduction

A site walkover was conducted by Hydrogeo in order to identify surface water features and gain an understanding of the general site layout relevant to drainage.

Photographs taken during the site walkover have been shown in Table 3-1. A plan of the photograph locations has been shown in Drawing 3.

**Table 3-1 Site walkover photographs**

| Reference | Description                                                                 | Photograph                                                                           |
|-----------|-----------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| 1         | Looking north from the southern boundary of the northern parcel of land.    |   |
| 2         | Looking north from the south western corner of the northern parcel of land. |  |

| Reference | Description                                                                                                                                                                                                           | Photograph                                                                           |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| 3         | <p>Looking east from the western boundary of the northern parcel of land.</p> <p>The break of slope to the flat section of this area of the Site is visible.</p>                                                      |    |
| 4         | <p>Looking south from the north eastern corner of the northern parcel of land.</p>                                                                                                                                    |   |
| 5         | <p>Culvert conveying a watercourse towards the north east.</p> <p>Entrance to the culvert is located outside site boundary but within the Client ownership boundary. (drain survey from this location undertaken)</p> |  |

## 4 Surface Water Drainage

---

### 4.1 Introduction

This drainage statement complies with the principles of SuDS in Wales presented in the 'Statutory Standards for Sustainable Drainage Systems – Designing, constructing, operating and maintaining surface water drainage systems'.

The six standards that need to be met are as follows:

- S1 – Surface water run-off destination
- S2 – Surface water runoff hydraulic control
- S3 – Water Quality
- S4 – Amenity
- S5 – Biodiversity
- S6 – Designing drainage for construction, operation, maintenance and structural integrity.

A sustainable drainage system is designed to replicate, as closely as possible, the natural drainage from a site (before development) to ensure that the flood risk downstream of the Site does not increase as a result of the land being developed. SuDS can also significantly improve the quality of water leaving a site and can enhance the amenity and biodiversity that a site has to offer.

Projections of future climate change in the UK, indicate more frequent, short-duration, high intensity rainfall and more frequent periods of long duration rainfall. As such, the recommended national precautionary sensitivity range for peak rainfall intensity is 40%.

## 5 S1: Surface Water Run-Off Destination

---

### 5.1 Introduction

As part of the SuDS Standards the management of run-off from developments should be prioritised as to the choice of discharge destination. The priority hierarchy is listed below:

1. Collect for re-use;
2. Infiltrate to ground;
3. Discharge to a surface water body;
4. Discharge to a surface water sewer/highway drain;
5. Discharge to a combined sewer.

### 5.2 Collect for re-use

The reuse of water from roofed areas to provide grey (non-potable) water for toilet flushing and washing can reduce storm run-off without the need for treatment or oil separators as the risk of spillage or contamination is low.

It is expected that there will be a demand for water at development for use in toilet flushing and potentially a washing machine, however the yield is expected to exceed demand. As such, rain water harvesting is unlikely to be a viable or cost-effective method of managing surface water run-off.

Small amounts of surface water run-off from the developed building roof can be collected and stored in water butts provided at each property for future use in the gardens.

### 5.3 Infiltrate to ground

Soakaway testing was undertaken on land directly adjacent to the site in 2017 to support the Access Road Drainage Statement (Appendix E). The test results provide an indication of the potential infiltration rates in the part of the site near the access road. Infiltration rates were measured between  $4.39 \times 10^{-5}$  m/s and  $4.71 \times 10^{-5}$  m/s. No groundwater was encountered in trial pits excavated to 2.7m depth. This does indicate that some infiltration SuDS techniques, such as soakaways could be included in the scheme as viable method of surface water discharge, following further testing.

### 5.4 Discharge to a surface water body

The small stream which passes beneath the site in the north in a culvert is considered to be a viable option for drainage discharge at the Site.

## **5.5 Discharge to sewers**

A private surface water sewer flows onto the site from Llanellen village and discharges to the culverted watercourse. Due to the proximity of the existing culverted watercourse, discharge to sewers is not a required drainage option for the Site at this time.

## 6 S2: Surface Water Run-Off Hydraulic Control

---

### 6.1 Introduction

The objective of this drainage strategy is to ensure that a sustainable drainage solution can be achieved which reduces the peak discharge rate to manage and reduce the flood risk posed by the surface water run-off from the development of the Site. The drainage strategy takes into account the following principles.

- No increase in the volume or rate of surface water run-off from the development of the Site;
- No increase in flooding to people or property off-Site as a result of the development of the Site;
- The proposals take into account a 40% increase in rainfall intensity due to climate change during the next 100 years;
- The proposals take into account a 10% increase in impermeable surfaces as a result of urban creep.

### 6.2 Site Areas

The current Site areas have been calculated from satellite imagery and the Site visit, the end-Site areas have been calculated from the proposed layout plans given to Hydrogeo by the Client team and attached as Appendix A.

The total area of the development Site has been calculated to be approximately 34,000m<sup>2</sup>. The Site is currently greenfield used primarily for grazing. The proposal is for a residential development with driveways, access roads, footpaths and soft landscaped areas. The roofs of the buildings and tarmac access road would be impermeable, however pavements, patios, driveways and footpaths would be constructed as permeable surfaces. The total impermeable area at the end-Site will have increased.

These Site areas are summarised in Table 6-1, and show that the area of impermeable surfaces on Site is planned to increase.

**Table 6-1 – Site features and surfaces.**

| Feature                   | Current Area (m <sup>2</sup> ) | Proposed Area (m <sup>2</sup> ) | Permeability |
|---------------------------|--------------------------------|---------------------------------|--------------|
| Total Site                | 35,280                         | 35,280                          | Mixed        |
| Roofs                     | 0.0                            | 2,926                           | Impermeable  |
| Garages                   | 0.0                            | 280                             | Impermeable  |
| Access Road               | 0.0                            | 1,675                           | Impermeable  |
| External patios/paths     | 0.0                            | 1,280                           | Permeable    |
| Pavement/pathways/parking | 0.0                            | 3,375                           | Permeable    |
| Grass/Soft Landscaping    | 35,280                         | 25,744                          | Permeable    |

### 6.3 Surface Water Run-Off Rates

For discharge to a surface water body an analysis of the current surface water run-off rates from the Site is required to be made using the appropriate hydraulic modelling software.

As the Site is a greenfield site, the surface water run-off rate has been calculated Causeway Flow. The full calculations are attached as Appendix C.

### 6.4 Surface Water Attenuation Estimation

An estimation of surface water run-off volume is required to permit effective surface water management and prevent any increase in flood risk to off-Site receptors.

According to regulations, the sizing of surface water drainage features must be calculated based on the volume of surface water run-off during a 1 in 100-year rainfall event. The calculations must also take into account a 40% increase in future rainfall due to climate change, as well as a 10% increase in impermeable surfaces on Site due to urban creep. Site specific rainfall design data was obtained from the Flood Estimation Handbook (FEH) web service.

The surface water run-off storage volume has been calculated using Causeway Flow, and the full results from this tool are attached as Appendix C.

The tool calculates that a 1m deep attenuation basin would require a surface area of approximately 1800m<sup>2</sup>.

## 6.5 Drainage Strategy

At this stage a detailed surface water drainage design has not been undertaken, however it is necessary to demonstrate that the surface water from the proposed development can be discharged safely and sustainably. The surface water drainage strategy at the Site will include the following:

- Interception, treatment and attenuation of surface water run-off;
- Restricted discharge from the Site, set to the greenfield 1 in 100-year run-off rate.

Interception, treatment and attenuation of the surface water run-off will be provided by the permeable paving surfaces, plot scale rain gardens and a grassy detention basin.

Outflow from the detention basin will be restricted via a flow control device. The outflow will then be transported via underground pipes to the northern part of the site to a new connection with the existing culverted watercourse within the ownership boundary.

The proposed surface water drainage layout within the development Site boundary is presented in Drawing 4.

## 6.6 Interception

The interception of the first 5mm of rainfall at the Site will be provided by a combination of the permeable surfaces, plot scale rain gardens and a grassy detention basin.

According to the Welsh standards, all permeable surfaces, whether lined or not, can be assumed to provide interception provided there is no additional area drained to them. The standards also state that rain gardens can provide interception where the impermeable surface area being drained is less than 5 times the vegetated surface area receiving the run-off.

Pedestrian areas and parking areas, will be permeable surfaces to provide interception. The run-off from the impermeable surfaces (roofs) will be directed through the permeable surfaces to the rain gardens to provide the interception. The permeable surfaces will be able to provide temporary storage for the surface water run-off, decreasing the required size of the attenuation feature.

## 6.7 Designing for Local Drainage System Failure/Design Exceedance

When considering residual risk, it is necessary to make predictions as to the impacts of a storm event that exceeds the design event, or the impact of a failure of the local drainage system. The drainage strategy applies a safe and sustainable approach to discharging

rainfall run-off from the Site and this reduces the risk of flooding. However, it is not possible to completely remove the risk. This section is therefore associated with the way the residual risk is managed.

As part of the drainage strategy, it must be demonstrated that the flooding of property would not occur in the event of local drainage system failure and/or design exceedance. It is not economically viable or sustainable to build a drainage system that can accommodate the most extreme events. Consequently, the capacity of the drainage system may be exceeded on rare occasions, with excess water flowing above ground.

The drainage components would be designed to accommodate the 1 in 100-year critical rainfall event plus an allowance for climate change and urban creep. Flows from an exceedance event (>1 in 100-year rainfall event) and/or component failure are expected to result in overtopping of the subbases. Any surface water run-off from the Site would be expected to flow east onto the public road and not towards any properties. The risk to the proposed development from flooding as a result of an exceedance event or system failure is negligible.

## 7 S3: Water Quality

The Simple Index Approach Tool from the SuDS Manual has been used to assess the pollution mitigation capacity of the proposed SuDS features at the Site.

The pollution hazard level of different surfacing types has been shown in, based on Table G3.1 of the Welsh statutory standards and Table 26.2 of the SuDS Manual. The development is proposed to contain residential roofs, property driveways and car parking spaces and a shared access road.

**Table 7-1 - Potential pollution source and hazard indices.**

| Source                                                  | Hazard Level  | Total Suspended Solids | Metals | Hydrocarbons |
|---------------------------------------------------------|---------------|------------------------|--------|--------------|
| Residential roof                                        | Very low risk | 0.2                    | 0.2    | 0.05         |
| Low traffic roads/Residential driveways and car parking | Low risk      | 0.5                    | 0.4    | 0.4          |

Note – The indices range from 0 (no pollution hazard for this contaminant type) to 1 (high pollution for this contaminant type).

It is considered that the Site falls under the “low risk” level of hazard.

In order to deliver adequate treatment, the SuDS components should have a total pollution mitigation index for each contaminant type that is equal to or greater than the pollution hazard index for that contaminant type. Where SuDS components are used in a sequential train, a factor of 0.5 must be applied to each subsequent feature to account for the reduced performance.

It is assumed that all surface water run-off will first go through the permeable paving before entering the rain garden, therefore the same mitigation will be applied to all rainfall, and the mitigation of the rain garden will have a factor of 0.5 applied.

The pollution mitigation for discharges to surface waters for the SuDS components are shown in Table 7-2, based on Table 26.3 of the SuDS Manual.

**Table 7-2 – Mitigation indices for SuDS components.**

| Type of SuDS Component | Total Suspended Solids | Metals | Hydrocarbons |
|------------------------|------------------------|--------|--------------|
| Permeable Paving       | 0.7                    | 0.6    | 0.7          |
| Rain Garden            | 0.8                    | 0.8    | 0.8          |
| Detention basin        | 0.5                    | 0.5    | 0.6          |

Note – The indices range from 0 (no pollution mitigation for this contaminant type) to 1 (high pollution mitigation for this contaminant type).

The proposed SuDS features will be capable of mitigating any potential pollution from the surface water run-off before discharge to the local surface water course.

## **8 S4 & S5: Amenity and Biodiversity**

---

### **8.1 Amenity and Biodiversity Benefits**

The proposed development plans for the Site includes large areas of soft landscaping with the planting of native trees, native species hedgerows, residential lawns and public open space. These features will help support flora and fauna for the benefit of the development community, as well as providing air quality improvements in accordance with the SuDS Manual.

The proposed rain gardens to each individual dwelling plot will provide amenity and biodiversity benefits for the development as the vegetation will be native plants to help support the local flora and fauna.

## **9 S6: Designing Drainage for Construction, Operation, Maintenance and Structural Integrity**

---

### **9.1 Introduction**

The SuDS components have been designed for easy maintenance to comprise:

- Regular day-to-day care, such as regular land maintenance to control excessive vegetation growth and checking inlets where water enters the SuDS features;
- Occasional tasks, such as checking the SuDS features and removing any silt build-up;
- Remedial work, such as repairing damage where necessary.

### **9.2 SuDS Maintenance and Management**

A management and maintenance plan will be developed as part of the full design application. A construction and phasing plan to mitigate impacts of surface water run-off during construction and provided details of development phases will be developed with the full design application.

It is proposed that SuDS devices are constructed toward the very end of the development in order to prevent damage or silt build-up of the components.

### **9.3 Design Life**

The design life of the development is likely to exceed the design life of each of the SuDS components for the Site. During the routine inspections of any SuDS components, it may become apparent that they have reached the end of their functional lifetime. In the interest of sustainability, repairs should be the first choice of solution where possible. If this is not the case it will be necessary to undertake complete replacement of the component in question.

When undertaking maintenance, repairs or replacement, all engineering drawings used in the design, construction and installation of the SuDS components should be referred to for construction and specification details. This will help to ensure satisfactory performance of each of the SuDS components.

## 10 Conclusion

---

### 10.1 Introduction

Hydrogeo Limited (Hydrogeo) have been commissioned by the Trustees of Morspan Pension Scheme Ltd (the Client) to undertake a Surface Water Drainage Strategy Report for a parcel of land at Llanellen Court, Llanellen, Monmouthshire (the Site).

This report has been prepared to promote the Site for inclusion in the Monmouthshire County Council (MCC) Local Development Plan (LDP) for residential land use. In order for the Site to be subject to a successful future planning application the surface water discharges would need to meet current planning requirements.

### 10.2 Surface Water Drainage

The surface water drainage strategy ensures that a sustainable drainage solution can be achieved which reduces the peak discharge rate to manage and reduce the flood risk posed by the surface water run-off from development at the Site.

At this stage a detailed drainage design has not been undertaken, however it is necessary to demonstrate that the surface water from the proposed development can be discharged safely and sustainably.

The proposed development will incorporate a number of linked SuDS features including permeable surfaces, plot scale rain gardens and a grassy detention basin. The scheme will capture and treat surface water run-off from the impermeable surfaces on the developed Site and will then release this stored water at a set rate into the existing culverted watercourse that passes through the site.


## Drawings

---

## Drawing 1

---


### Surface water features plan



DRAWING 1  
Surface water features

- KEY**
- Site boundary
  - Pond
  - Elevation contour (mAOD)
  - Main River
  - Watercourse
  - Culverted watercourse (225mmØ )
  - Spring

© Microsoft [2021]  
Contains OS data © Crown copyright and database right [2021]




| Date    | By | Paper | Scale   | Rev |
|---------|----|-------|---------|-----|
| 12 2023 | TP | A3    | 1:3,000 | 2   |

## Drawing 2

---

### Flooding hazard plan



**DRAWING 2**  
Flooding hazard plan

**KEY**  
 Site boundary

 Main River

**Watercourse**  
**Flooding Hazard - Rivers**

 High Risk

 Medium Risk

 Low Risk


**Flooding Hazard - Surface Water**

 High Risk

 Medium Risk

 Low Risk

© Microsoft [2021]  
Contains OS data © Crown copyright and database right [2021]



| Date    | By | Paper | Scale   | Rev |
|---------|----|-------|---------|-----|
| 12 2023 | TP | A3    | 1:5,000 | 2   |

## Drawing 3

---


### Photo location plan



**DRAWING 3**  
Photo location plan

- KEY**
-  Site boundary
  -  Photo location

© Microsoft [2021]  
Contains OS data © Crown copyright and database right [2021]



| Date    | By | Paper | Scale   | Rev |
|---------|----|-------|---------|-----|
| 12 2023 | TP | A3    | 1:3,000 | 2   |

## **Drawing 4**

---

### **Drainage Layout**

DRAWING 4  
Surface water drainage plan

**KEY**

Site boundary (approximate)

**Existing drainage features**


--- Culverted watercourse

○ Manhole


**Proposed surface water drainage features**

Detention basin


--- Pipe



Rain gardens within plots and communal pedestrian areas



Drawing adapted from 'Site block plan as proposed', Reference: 1434 (3K) 01B, November 2023, Buckle Chamberlain Partnership



| Date    | By | Paper | Scale   | Rev |
|---------|----|-------|---------|-----|
| 12 2023 | TP | A3    | 1:1,100 | 1   |

## Appendices

---

## Appendix A

---

### Proposed site layout plan

| REF   | UNIT TYPE            | FLOOR AREA         | No |
|-------|----------------------|--------------------|----|
| A     | 2 BED / 4 PERSON     | 83.0m <sup>2</sup> | 4  |
| B     | 3 BED / 5 PERSON     | 94.0m <sup>2</sup> | 4  |
| C     | 2 BED / 4 PERSON     | 85.0m <sup>2</sup> | 4  |
| D     | 1 BED / 2 PERSON     | 52.0m <sup>2</sup> | 4  |
| E     | 4B / 7 PERSON        | 190m <sup>2</sup>  | 7  |
| F     | 4B / 7 PERSON        | 170m <sup>2</sup>  | 4  |
| G     | 5B / 8 PERSON        | 170m <sup>2</sup>  | 3  |
| H     | 5B / 5 PERSON (BUNG) | 120m <sup>2</sup>  | 2  |
| TOTAL |                      |                    | 32 |

AFFORDABLE (IGN)  
50%

OPEN MARKET (IGN)  
50%

DRAFT PLAN FOR COMMENT



REV: B NOV. 2023 GAB  
LAYOUT REVISED FOR 32 UNITS  
(16 AFFORDABLE, 16 OPEN MARKET)

**Buckle Chamberlain Partnership Ltd.**  
Architects & Architectural Technologists.

Mill House, Llancayo Court,  
Llancayo, Usk,  
Monmouthshire  
NP15 1HY  
Tel: 01291 672264  
01291 673424  
Fax: 01291 671050  
Email: enquiries@bucklechamberlain.co.uk

Client TRUSTEES OF MORSAN PENSION SCHEME

Project PROPOSED CANDIDATE SITE AT  
LLANELLEN COURT, LLANELLEN,  
ABERGAVENNY  
(NORTH SITE PROPOSAL)

Drawing SITE BLOCK PLAN  
AS PROPOSED


Date NOV. 2023 Scale 1:1000

Drawn by GAB Drawing No  
Checked by 1434 (SK) OIB  
Status

## Appendix B

---

### DCWW sewer plan





**Dŵr Cymru  
Welsh Water**

PPA0005955 Sewer Plan



**LEGEND(Representative of most common features)**

|                       |                                                       |                         |                 |
|-----------------------|-------------------------------------------------------|-------------------------|-----------------|
| <b>Waste network:</b> | Foul chamber                                          | Surface water chamber   | Outfall         |
| Combined chamber      | Combined sewer overflow                               | Special purpose chamber | Treatment works |
| Pumping station       | Private sewer subject to Sect. 104 adoption agreement | Private Sewer Transfer  | Lateral Drain   |
| Inspection Chamber    |                                                       |                         |                 |

NB: Sewer symbol colour indicates the type.  
RED - Combined  
GREEN - Surface Water  
BROWN - Foul  
Purple - Former S24 sewers (for indicative purposes only)

**Notes:**

Whilst every reasonable effort has been taken to correctly record the pipe material of DCWW assets, there is a possibility that in some cases pipe material (other than Asbestos Cement or Pitch Fibre) may be found to be asbestos cement (AC) or Pitch Fibre (PF). It is therefore advisable that the possible presence of AC or PF pipes be anticipated and considered as part of any risk assessment prior to excavation

Dŵr Cymru Cylchgrwyd (the Company) gives the information as to the position of its underground apparatus by way of general guidance only and on the understanding that it is based on the best information available and no warranty as to its correctness is made upon it in the event of excavations or other works made in the vicinity of the Company's apparatus. The onus of locating apparatus before carrying out any excavations rests entirely on you. The information which is supplied by the Company is done so in accordance with statutory requirements of sections 199 and 199A of the Water Industry Act 1991 which is based upon the best information available and, in particular, but without prejudice to the generality of the foregoing, it should be noted that the records that are available to the Company may not disclose the existence of a water main, service pipe, sewer, lateral drain or disposal main and any associated apparatus laid before 1 September 1989, or, if they do, the particulars thereof including their position underground may not be accurate. It must be understood that the furnishing of this information is entirely without prejudice to the provision of the New Roads and Street Works Act 1991 and the Company's right to be compensated for any damage to its apparatus.

Service pipes are not generally shown but their presence should be anticipated.

**EXACT LOCATIONS OF ALL APPARATUS  
TO BE DETERMINED ON SITE.**

Reproduced by permission of the Ordnance Survey on behalf of  
HMISO. © Crown copyright and database right 2017.  
All rights reserved.  
Ordnance Survey Licence number 100019534

Map Ref: 330250,210575  
Map scale: 1:1250  
Printed by: Jonathan Hobson  
Printed on: 20 Aug 2021

## Appendix C

---

### Causeway Flow Calculations

### Design Settings

|                                      |        |                                    |               |
|--------------------------------------|--------|------------------------------------|---------------|
| Rainfall Methodology                 | FEH-22 | Minimum Velocity (m/s)             | 1.00          |
| Return Period (years)                | 100    | Connection Type                    | Level Soffits |
| Additional Flow (%)                  | 0      | Minimum Backdrop Height (m)        | 0.200         |
| CV                                   | 1.000  | Preferred Cover Depth (m)          | 1.200         |
| Time of Entry (mins)                 | 5.00   | Include Intermediate Ground        | ✓             |
| Maximum Time of Concentration (mins) | 30.00  | Enforce best practice design rules | ✓             |
| Maximum Rainfall (mm/hr)             | 50.0   |                                    |               |

### Nodes

| Name  | Area<br>(ha) | T of E<br>(mins) | Cover<br>Level<br>(m) | Easting<br>(m) | Northing<br>(m) | Depth<br>(m) |
|-------|--------------|------------------|-----------------------|----------------|-----------------|--------------|
| Basin | 1.033        | 5.00             | 53.000                | 330379.000     | 210644.000      | 1.000        |

### Simulation Settings

|                      |        |                            |     |                          |     |
|----------------------|--------|----------------------------|-----|--------------------------|-----|
| Rainfall Methodology | FEH-22 | Drain Down Time (mins)     | 240 | 100 year (l/s)           | 5.7 |
| Summer CV            | 1.000  | Additional Storage (m³/ha) | 0.0 | Check Discharge Volume   | ✓   |
| Winter CV            | 1.000  | Check Discharge Rate(s)    | ✓   | 100 year 360 minute (m³) | 266 |
| Analysis Speed       | Normal | 1 year (l/s)               | 2.3 |                          |     |
| Skip Steady State    | x      | 30 year (l/s)              | 4.7 |                          |     |

### Storm Durations

|    |    |    |     |     |     |     |     |     |     |     |      |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|------|
| 15 | 30 | 60 | 120 | 180 | 240 | 360 | 480 | 600 | 720 | 960 | 1440 |
|----|----|----|-----|-----|-----|-----|-----|-----|-----|-----|------|

| Return Period<br>(years) | Climate Change<br>(CC %) | Additional Area<br>(A %) | Additional Flow<br>(Q %) |
|--------------------------|--------------------------|--------------------------|--------------------------|
| 2                        | 40                       | 10                       | 0                        |
| 30                       | 40                       | 10                       | 0                        |
| 100                      | 40                       | 10                       | 0                        |

### Pre-development Discharge Rate

|                              |            |                        |      |
|------------------------------|------------|------------------------|------|
| Site Makeup                  | Greenfield | Growth Factor 30 year  | 1.80 |
| Greenfield Method            | FEH        | Growth Factor 100 year | 2.18 |
| Positively Drained Area (ha) | 1.033      | Betterment (%)         | 0    |
| SAAR (mm)                    | 1139       | QMed                   | 2.4  |
| Host                         | 6          | QBar                   | 2.6  |
| BFIHost                      | 0.812      | Q 1 year (l/s)         | 2.3  |
| Region                       | 9          | Q 30 year (l/s)        | 4.7  |
| QBar/QMed conversion factor  | 1.075      | Q 100 year (l/s)       | 5.7  |
| Growth Factor 1 year         | 0.88       |                        |      |

### Pre-development Discharge Volume

|                              |            |                       |       |
|------------------------------|------------|-----------------------|-------|
| Site Makeup                  | Greenfield | Return Period (years) | 100   |
| Greenfield Method            | FSR/FEH    | Climate Change (%)    | 0     |
| Positively Drained Area (ha) | 1.033      | Storm Duration (mins) | 360   |
| Soil Index                   | 2          | Betterment (%)        | 0     |
| SPR                          | 0.30       | PR                    | 0.353 |
| CWI                          | 125.348    | Runoff Volume (m³)    | 266   |

Node Basin Online Orifice Control

|                          |        |                   |       |                       |       |
|--------------------------|--------|-------------------|-------|-----------------------|-------|
| Flap Valve               | x      | Design Depth (m)  | 1.000 | Discharge Coefficient | 0.600 |
| Replaces Downstream Link | ✓      | Design Flow (l/s) | 2.3   |                       |       |
| Invert Level (m)         | 52.000 | Diameter (m)      | 0.033 |                       |       |

Node Basin Depth/Area Storage Structure

|                             |         |               |      |                           |        |
|-----------------------------|---------|---------------|------|---------------------------|--------|
| Base Inf Coefficient (m/hr) | 0.00000 | Safety Factor | 10.0 | Invert Level (m)          | 52.000 |
| Side Inf Coefficient (m/hr) | 0.00000 | Porosity      | 1.00 | Time to half empty (mins) |        |

| Depth (m) | Area (m²) | Inf Area (m²) | Depth (m) | Area (m²) | Inf Area (m²) |
|-----------|-----------|---------------|-----------|-----------|---------------|
| 0.000     | 1400.0    | 0.0           | 1.000     | 1826.2    | 0.0           |

**Results for 2 year +40% CC +10% A Critical Storm Duration. Lowest mass balance: 99.99%**

| Node Event         | US<br>Node | Peak<br>(mins) | Level<br>(m) | Depth<br>(m) | Inflow<br>(l/s) | Node<br>Vol (m³) | Flood<br>(m³) | Status |
|--------------------|------------|----------------|--------------|--------------|-----------------|------------------|---------------|--------|
| 1440 minute winter | Basin      | 1440           | 52.494       | 0.494        | 24.0            | 743.0314         | 0.0000        | OK     |

| Link Event<br>(Upstream Depth) | US<br>Node | Link    | Outflow<br>(l/s) | Discharge<br>Vol (m³) |
|--------------------------------|------------|---------|------------------|-----------------------|
| 1440 minute winter             | Basin      | Orifice | 1.6              | 105.3                 |

**Results for 30 year +40% CC +10% A Critical Storm Duration. Lowest mass balance: 99.99%**

| Node Event         | US<br>Node | Peak<br>(mins) | Level<br>(m) | Depth<br>(m) | Inflow<br>(l/s) | Node<br>Vol (m³) | Flood<br>(m³) | Status |
|--------------------|------------|----------------|--------------|--------------|-----------------|------------------|---------------|--------|
| 1440 minute winter | Basin      | 1440           | 52.838       | 0.838        | 41.7            | 1323.2760        | 0.0000        | OK     |

| Link Event<br>(Upstream Depth) | US<br>Node | Link    | Outflow<br>(l/s) | Discharge<br>Vol (m³) |
|--------------------------------|------------|---------|------------------|-----------------------|
| 1440 minute winter             | Basin      | Orifice | 2.1              | 140.1                 |

**Results for 100 year +40% CC +10% A Critical Storm Duration. Lowest mass balance: 99.99%**

| Node Event         | US<br>Node | Peak<br>(mins) | Level<br>(m) | Depth<br>(m) | Inflow<br>(l/s) | Node<br>Vol (m³) | Flood<br>(m³) | Status |
|--------------------|------------|----------------|--------------|--------------|-----------------|------------------|---------------|--------|
| 1440 minute winter | Basin      | 1440           | 52.985       | 0.985        | 49.6            | 1586.0590        | 0.0000        | OK     |

| Link Event<br>(Upstream Depth) | US<br>Node | Link    | Outflow<br>(l/s) | Discharge<br>Vol (m³) |
|--------------------------------|------------|---------|------------------|-----------------------|
| 1440 minute winter             | Basin      | Orifice | 2.2              | 152.8                 |


## Appendix D

---

### Drainage Survey and Topographic Survey

A2

- Notes:
1. This drawing is copyright and its use or reproduction without the written permission of PM Consultants (UK) Ltd is prohibited
  2. Due to unavoidable inaccuracies during the reproduction process these drawings should not be scaled. Where dimensions are critical PM Consultants (UK) Ltd should be requested to confirm dimensions based on survey information. Scales appearing at the base of this plan are for indicative purposes only.
  3. This plan has been prepared in accordance with B.S. 1192, Part 1 in relation to scale and dimension. Tolerances permitted within the British Standard should be observed.
  4. All dimensions and particulars should be checked on site. Any discrepancies should be reported to PM Consultants (UK) Ltd before any work commences.



NOTES:

LEVELS AND CO-ORDINATE GRID ARE RELATED TO GPS SURVEY DATUM DERIVED FROM ORDNANCE SURVEY DATUM VIA OSTN15.

ALTHOUGH O.S. CO-ORDINATES ARE SHOWN ON THIS PLAN THE GRID IS TO BE TREATED AS ARBITRARY.

NO SCALE FACTOR HAS BEEN APPLIED TO THE SURVEY THEREFORE THE CO-ORDINATES SHOWN ARE NOT TRUE O.S. CO-ORDINATES.

| ISSUE | REVISION | DATE |
|-------|----------|------|
|       |          |      |

|                                                                                                                  |                |              |                |                      |  |
|------------------------------------------------------------------------------------------------------------------|----------------|--------------|----------------|----------------------|--|
| Job: DRAINAGE SURVEY<br>LLANELLEN COURT FARM<br>LLANELLEN                                                        |                |              |                |                      |  |
| Scale: 1:500                                                                                                     | Date: 24/11/23 | Drawn By: EH | Checked By: NM | Job Ref: LCF/BCP/001 |  |
| Client: Buckle Chamberlain Partnership<br>Mill House, Llancayo Court<br>Llancayo, Usk<br>Monmouthshire, NP15 1HY |                |              |                |                      |  |



**PMCONSULTANTS (UK) LTD**  
48 Park Avenue, Abergavenny  
Monmouthshire, NP7 5SP  
Web: pmconsultants.co.uk Tel: (01873) 850667  
E-Mail: surveys@pmconsultants.co.uk






## Appendix E

---

### Llanellen Access Road Drainage Statement (2017)

Llanellen Court

Approved access road



Highway Drainage Statement

April 2017

Traffic and Transport Planning

---

## Contents

|   |                                  |   |
|---|----------------------------------|---|
| 1 | Introduction                     | 2 |
| 2 | Works associated with new access | 2 |
| 3 | Soakaway Design                  | 2 |

## Figures

|   |                        |   |
|---|------------------------|---|
| 1 | Location of Trial Pits | 3 |
|---|------------------------|---|

## Appendix

|   |                                          |    |
|---|------------------------------------------|----|
| A | Location of Soakaways and Catch-pits     | 4  |
| B | Soil Infiltration Rates                  | 5  |
| C | New Junction Soakaway and Catch-pit      | 17 |
| C | Access Road Soakaways and Catch-pits     | 22 |
| D | Detail of Soakaway Pit with Rigid Lining | 30 |

## 1 Introduction

- 1.1 The approved new access road to Llanellen Court is located on the west of Route A4042. Adjacent to the site the road has a west to east cross-fall away from the proposed access to a number of gullies which appear to drain into adjacent fields.
- 1.2 The junction of the access road with the trunk road will be located at the bellmouth of an existing field gate approximately 10 metres wide and 5 metre deep. It falls away from the road so surface run-off drains into the adjacent field.
- 1.3 10m south of the new access junction a lay-by extends for some 30m to the existing access to Llanellen Court which drains towards the trunk road. Neither the lay-by nor the existing access road has drainage gullies.

## 2 Works associated with new access

- 2.1 When the new access road has been constructed the lay-by will become a grass verge and there will be little or no run-off onto A.4042. The existing access to Llanellen Court adjacent to the lay-by will be closed off, grubbed up and seeded so there will be no run-off onto the trunk road.
- 2.2 A section of access road will be adopted by Welsh Government. The boundary between the public and private highways will be marked by the installation of gullies on both sides of the road which will drain into soakaway SA1 designed to BRE Digest 365 standards (Appendix A). From this point the road will continue to slope away from the trunk road until it reaches a low point some 10m from the adopted boundary. Gullies will be installed on both sides of the road draining into soakaway SA2 (Appendix A).
- 2.3 From this point gullies will be constructed on both sides of the road at appropriate intervals draining into soakaways SA3 and SA4 (Appendix A).


## 3 Soakaway Design

- 3.1 Soil infiltration tests were carried out in accordance with BRE Digest 365 Soakaway Design on April 4, 5 and 6 2017 and the weather was dry. Two trial pits were excavated to a depth of approximately 2.7m at the locations shown in Fig 1. The pits had vertical sides trimmed square and groundwater was absent. They were filled three times with water to the invert level using a water bowser. The time taken for the water level to drain from invert level to empty was observed and recorded. The infiltration rates calculated for TP1 and TP2 were  $4.39 \times 10^{-5}$  and  $4.707 \times 10^{-5}$  respectively (Appendix B)
- 3.3 The soakaway pit (SA1) that will serve the new junction will be 6.1x6.1x2.8 metres with a 1.2m diameter concrete chamber and the catch-pit (CP1) will be a 1.2m diameter concrete chamber (Appendix C).
- 3.4 The soakaway pit (SA2) serving the access road near the new junction will be 5.80x5.80x3.2 metres with a 1.2m concrete chamber and the catch-pit (CP2) will be similar to CP1.
- 3.5 The dimensions for each soakaway will be based on standard detail (Appendix E).



Fig 1 Location of Trial Pits

## Appendix A Location of Soakaways and Catch-pits




## Appendix B Soil Infiltration Rates

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |                    |       |                                                   |             |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------------|-------|---------------------------------------------------|-------------|
| <b>Project</b> MORSPAN HOLDINGS LTD<br>PROPOSED ACCESS ROAD AT<br>LLANELLEN COURT, LLANELLEN<br>ABERGAVENNY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |              |                    |       | <b>TRAFFIC<br/>AND<br/>TRANSPORT<br/>PLANNING</b> |             |
| <b>Element</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | DRAINAGE     | <b>Project No.</b> | C2155 | <b>Sheet No.</b><br>1 of 12                       | <b>Rev.</b> |
| <b>Ref.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Calculations |                    |       | Output                                            |             |
| <p><u>SOIL INFILTRATION RATE</u></p> <p>Soil infiltration tests were carried out in accordance with BRE 365.</p> <p>Two trial pits were dug at locations indicated on Fig1. after trimming of the sides both TP1 &amp; TP2 were:-<br/>2.2m long x 1.3m wide x 2.7m deep (max)</p> <p>Because the base of the trial pits could not be cleaned effectively an O/A depth of 2.6m was adopted.</p> <p>The trial pits were filled 3 times and the time for the water to drain from the max effective depth (1.5m below GL) to empty was recorded, ref:- site record sheets TP1 &amp; TP2, from these record sheets graphs were plotted for each set of results, reference graphs TP1/1 to TP1/3 and TP2/1 to TP2/3.</p> <p><u>From BRE 365</u></p> <p>soil infiltration rate <math>f = \frac{V_{p75-25}}{a_{p50} \times t_{p75-25}}</math></p> <p>where <math>V_{p75-25}</math> = effective storage volume water between 75% &amp; 25% effective depth <math>\frac{m^3}{m^2}</math></p> |              |                    |       |                                                   |             |
| <b>Calculations</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |              | <b>Revision</b>    |       |                                                   |             |
| By                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Date         | By                 | Date  | Checked                                           | By          |
| DA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 14/2/17      |                    |       |                                                   |             |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |              |                    |       |                                                   | Checked     |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |              |                 |                    |                                                                                                                                                                                                                                                                                                 |        |                             |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------------|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|-----------------------------|
| <b>Project</b> MORSPAN HOLDINGS LTD<br>PROPOSED ACCESS ROAD AT<br>LLANELLEN COURT, LLANELLEN<br>ABERGAVENNY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |              |                 |                    | <b>TRAFFIC<br/>AND<br/>TRANSPORT<br/>PLANNING</b>                                                                                                                                                                                                                                               |        |                             |
| <b>Element</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | DRAINAGE     |                 | <b>Project No.</b> | C2155                                                                                                                                                                                                                                                                                           |        | <b>Sheet No.</b><br>2 of 12 |
| <b>Ref.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Calculations |                 |                    |                                                                                                                                                                                                                                                                                                 | Output |                             |
| <p>BRE 365 cont'd</p> <p><math>ap_{50}</math> = internal surface area of trial pit<br/>upto 50% effective depth inc.<br/>base area</p> <p><math>tp_{75-25}</math> = time for water to fall from<br/>75% to 25% effective storage<br/>depth</p> <p><u>CALCULATIONS</u></p> <p>IL of incoming pipe approx 1.5m<br/>below GL.</p> <p>common to both trial pits</p> <p>Effective storage depth<br/>= 2.6 - 1.5m = 1.1m</p> <p>Level @ 75% Full = <math>\frac{1.1}{4} + 1.5 = 1.775m</math></p> <p>Level @ 25% Full = <math>(\frac{1.1}{4} \times 3) + 1.5 = 2.325m</math></p> <p><math>\therefore V_{p75-25} = 2.2 \times 1.3 \times (2.325 - 1.775) = 1.573 m^3</math></p> <p><math>\therefore ap = (2.2 \times 0.55 \times 2) + (1.3 \times 0.55 \times 2) + (2.2 \times 1.3)</math><br/>= 2.42 + 1.43 + 2.86 = 6.71 m<sup>2</sup></p> <p><u>Graph TP1/1</u></p> <p><math>+75-25 = 90-15 = 75mm</math></p> <p><math>\therefore f_{TP1/1} = \frac{1.573}{6.71 \times 75 \times 60} = 5.21 \times 10^{-5}</math></p> |              |                 |                    | <p>m<sup>2</sup></p> <p>sec.</p> <p>Max effective<br/>depth 1.5m</p> <p>Effective storage<br/>depth 1.1m</p> <p>75% Full = 1.775m</p> <p>25% Full = 2.325m</p> <p><math>V_{p75-25} = 1.573 m^3</math></p> <p><math>ap = 6.71 m^2</math></p> <p><math>f_{TP1/1} = 5.21 \times 10^{-5}</math></p> |        |                             |
| <b>Calculations</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |              | <b>Revision</b> |                    |                                                                                                                                                                                                                                                                                                 |        |                             |
| By                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | Date         | By              | Date               | Checked                                                                                                                                                                                                                                                                                         | By     | Checked                     |
| AD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 14/4/17      |                 |                    |                                                                                                                                                                                                                                                                                                 |        |                             |

|                                                                                                                                                                                          |                 |             |       |                                                   |         |      |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|-------------|-------|---------------------------------------------------|---------|------|
| <b>Project</b> MORSPAN HOLDINGS LTD<br>PROPOSED ACCESS ROAD AT<br>LLANELLEN COURT, LLANELLEN<br>ABERGAYENNY                                                                              |                 |             |       | <b>TRAFFIC<br/>AND<br/>TRANSPORT<br/>PLANNING</b> |         |      |
| Element                                                                                                                                                                                  | DRAINAGE        | Project No. | C2155 | Sheet No.<br>3 of 12                              | Rev.    |      |
| Ref.                                                                                                                                                                                     | Calculations    |             |       | Output                                            |         |      |
| <u>CALCULATIONS cont'd</u><br><br><u>Graph TP1/2</u><br>$t_{75-25} = 118 - 31 = 87 \text{ min}$<br>$\therefore f_{TP1/2} = \frac{1.573}{6.71 \times 87 \times 60} = 4.49 \times 10^{-5}$ |                 |             |       | $f_{TP1/2} = 4.49 \times 10^{-5}$                 |         |      |
| <u>Graph TP1/3</u><br>$t_{75-25} = 111 - 22 = 89 \text{ min}$<br>$\therefore f_{TP1/3} = \frac{1.573}{6.71 \times 89 \times 60} = 4.39 \times 10^{-5}$                                   |                 |             |       | $f_{TP1/3} = 4.39 \times 10^{-5}$                 |         |      |
| <u>For TP1 use <math>f = 4.39 \times 10^{-5}</math></u>                                                                                                                                  |                 |             |       | <u>TP1 <math>f = 4.39 \times 10^{-5}</math></u>   |         |      |
| <u>Graph TP2/1</u><br>$t_{75-25} = 98 - 33 = 65 \text{ min}$<br>$\therefore f_{TP2/1} = \frac{1.573}{6.71 \times 65 \times 60} = 6.011 \times 10^{-5}$                                   |                 |             |       | $f_{TP2/1} = 6.011 \times 10^{-5}$                |         |      |
| <u>Graph TP2/2</u><br>$t_{75-25} = 124 - 47 = 77 \text{ min}$<br>$\therefore f_{TP2/2} = \frac{1.573}{6.71 \times 77 \times 60} = 5.074 \times 10^{-5}$                                  |                 |             |       | $f_{TP2/2} = 5.074 \times 10^{-5}$                |         |      |
| <u>Graph TP2/3</u><br>$t_{75-25} = 126 - 43 = 83 \text{ min}$<br>$\therefore f_{TP2/3} = \frac{1.573}{6.71 \times 83 \times 60} = 4.707 \times 10^{-5}$                                  |                 |             |       | $f_{TP2/3} = 4.707 \times 10^{-5}$                |         |      |
| <u>For TP2 Use <math>f = 4.707 \times 10^{-5}</math></u>                                                                                                                                 |                 |             |       | <u>TP2 <math>f = 4.707 \times 10^{-5}</math></u>  |         |      |
| Calculations                                                                                                                                                                             |                 | Revision    |       |                                                   |         |      |
| By<br>DA                                                                                                                                                                                 | Date<br>14/4/17 | By          | Date  | Checked                                           | By      | Date |
|                                                                                                                                                                                          |                 |             |       |                                                   | Checked |      |

FIG 1 4/12



5/12

9

---

Traffic and Transport Planning

TRIAL PIT NO 1  
TEST 1

TP/1/1 6/12

MAX EFFECTIVE DEPTH

75% FULL

25% FULL


EMPTY


15 MIN

30 MIN

DEPTH (M) BELOW GL

TIME (MIN) TO EMPTY





TP1/3

8/12

TRIAL PIT NO 1  
TEST 3

MAX EFFECTIVE DEPTH

75% FULL

25% FULL


EMPTY

DEPTH (M) BELOW GL

111 MIN

22 MIN

TIME (MIN) TO EMPTY




TP 2

9/12

13


---

Traffic and Transport Planning




TP/2/2 11/12

TRIAL PIT NO 2  
TEST 2



TP2 / 3 12/12


TRIAL PIT 1502  
TEST 3



## Appendix C New Junction Soakaway and Catch-pit

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                               |                    |       |                                                                                                                                                                                                                           |        |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--------------------|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------|
| <b>Project</b> MORSAN HOLDINGS LTD<br>PROPOSED ACCESS ROAD AT<br>LLANELLEN COURT, LLANELLEN<br>ABERGAVENNY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                               |                    |       | <b>TRAFFIC<br/>AND<br/>TRANSPORT<br/>PLANNING</b>                                                                                                                                                                         |        |
| <b>Element</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | SECTION 278 WORKS<br>DRAINAGE | <b>Project No.</b> | C2155 | <b>Sheet No.</b>                                                                                                                                                                                                          | Rev.   |
| <b>Ref.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Calculations                  |                    |       | 1 of 5                                                                                                                                                                                                                    | Output |
| <u>SOAKAWAY DESIGN</u><br>Spreadsheet used in design based on BRE 365 method.<br>Ref. Test spreadsheet based on design example page 7 (Sheet 5/5)<br><u>Soakaway SAI</u><br>Max. area of new junction draining to gullies located at extent of 278 works<br>$= 500 \text{ m}^2$ (Reference Fig 2)<br>Effective depth soakaway 1.1m<br>$f = 4.39 \times 10^{-5}$ (Trial Pit N°1)<br>Dia soakaway chamber 1200 mm dia<br>Wall thickness of chamber ring 70mm<br>r from 'The Wallingford Procedure Vol 3 Maps' Ratio of M5-60 min to M5-two day rainfalls $= 0.25$<br>From input, results of spreadsheet indicate a critical size soakaway $= 6.05 \times 6.05 \text{ m}$<br>and time to empty 50% $= 3.06 \text{ hrs.}$ |                               |                    |       | <u>Input to Spreadsheet</u><br>$A = 500 \text{ m}^2$<br>$d = 1.1 \text{ m}$<br>$f = 4.39 \times 10^{-5}$<br>$D1 = 1.2 \text{ m}$<br>$T_{\text{wall}} = 0.07 \text{ m}$<br>$r = 0.25$<br><br>$< 24 \text{ hrs}$<br>BRE 365 |        |
| <b>Calculations</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                               | <b>Revision</b>    |       |                                                                                                                                                                                                                           |        |
| By                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Date                          | By                 | Date  | Checked                                                                                                                                                                                                                   |        |
| DA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | 14/4/17                       |                    |       |                                                                                                                                                                                                                           |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                               | By                 | Date  | Checked                                                                                                                                                                                                                   |        |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                               |                    |       |                                                                                                                                                                                                                           |        |

|                                                                                                                                                                                                                                                                                                                 |                               |             |       |                                                                                                                                                                                                       |      |         |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|-------------|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|---------|
| <b>Project</b> MORSAN HOLDINGS LTD<br>PROPOSED ACCESS ROAD AT<br>LLANELLEN COURT, LLANELLEN<br>ABERGAVENNY                                                                                                                                                                                                      |                               |             |       | <b>TRAFFIC<br/>AND<br/>TRANSPORT<br/>PLANNING</b>                                                                                                                                                     |      |         |
| Element                                                                                                                                                                                                                                                                                                         | SECTION 278 WORKS<br>DRAINAGE | Project No. | C2155 | Sheet No.<br>2 of 5                                                                                                                                                                                   | Rev. |         |
| Ref.                                                                                                                                                                                                                                                                                                            | Calculations                  |             |       | Output                                                                                                                                                                                                |      |         |
| <u>Soakaway SAI cont'd</u><br><br><u>Make soakaway pit 6.10 m sq.</u><br>chamber 1200 mm dia<br>GL Approx 49.00 m<br>IL Inlet pipe 47.46 m<br>Top Base 46.21 m.<br><br><u>Catch Pit CPI</u><br>chamber 1200 mm dia<br>GL Approx 49.00 m<br>IL Inlet pipe (150 dia) 47.65 m<br>IL Outlet pipe (225 dia) 47.575 m |                               |             |       | <u>SAI</u><br><u>Size</u><br><u>6.10 m sq.</u><br>1.2 m dia<br>GL 49.00<br>IL inlet 47.46 m<br>Top Base 46.21 m<br><br><u>CPI</u><br>1.2 m dia<br>GL 49.00 m<br>IL (150) 47.65 m<br>IL (225) 47.575 m |      |         |
| Calculations                                                                                                                                                                                                                                                                                                    |                               | Revision    |       |                                                                                                                                                                                                       |      |         |
| By<br>[Signature]                                                                                                                                                                                                                                                                                               | Date<br>14/4/17               | By          | Date  | Checked                                                                                                                                                                                               | By   | Date    |
|                                                                                                                                                                                                                                                                                                                 |                               |             |       |                                                                                                                                                                                                       |      | Checked |



4/5

Job No C2155  
Project Llanellen Court Access Road SOAKAWAY SA1

Date 13/04/17  
By DA

**SOAKAWAY DESIGN TO BRE 365**

|                        |                    |                                                                                                                            |
|------------------------|--------------------|----------------------------------------------------------------------------------------------------------------------------|
| A                      | 500 m <sup>2</sup> | Impermeable Surface Area of Catchment                                                                                      |
| f                      | 4.39E-05 m/sec     | Infiltration rate f of soil into which soakaway drains                                                                     |
| d                      | 1.1 m              | Effective storage depth of soakaway                                                                                        |
| VR                     | 0.3                | Free volume (void) ratio of fill to pit around rings                                                                       |
| Twall                  | 0.07 m             | Wall Thickness of rings                                                                                                    |
| D1                     | 1.2 m              | Internal diameter of Ring 1                                                                                                |
| Vol R1                 | 1.24               | Storage capacity of ring 1 ( $= 3.142 * (D1^{0.5})^2 * d$ m <sup>3</sup> )                                                 |
| Void R1                | 0.465              | Equivalent volume of Ring 1 (incl wall) at void ratio of outer fill ( $= 3.142 * (D1 + Twall)^2 * d * VR$ m <sup>3</sup> ) |
| D2                     | 0 m                | Internal diameter of Ring 2                                                                                                |
| Vol R2                 | 0.00               | Storage capacity of ring 2 ( $= 3.142 * (D2^{0.5})^2 * d$ m <sup>3</sup> )                                                 |
| Void R2                | 0.000              | Equivalent volume of Ring 2 (incl wall) at void ratio of outer fill ( $= 3.142 * (D2 + Twall)^2 * d * VR$ m <sup>3</sup> ) |
| M5-60 min              | 20 mm              | Base Rainfall                                                                                                              |
| D                      |                    | Storm duration (in minutes)                                                                                                |
| r                      | 0.25               | Rainfall ration (From BRE 365 Figure 1)                                                                                    |
| Z1                     |                    | Factor from BRE 365 Table 1 based on M5-D and 'r' from Fig 1                                                               |
| M5-D                   |                    | Total rainfall in design storm duration D for 5-year return period ( $= Z1 * D$ mm)                                        |
| Location               |                    | England and Wales                                                                                                          |
| Z2                     |                    | Factor from BRE 365 Table 2 based on M5-D                                                                                  |
| M10-D                  |                    | Total rainfall in design storm duration D for 10 year return period ( $= M5-D * Z2$ mm)                                    |
| R                      |                    | $= M10-D$                                                                                                                  |
| I                      |                    | Total inflow to soakaway ( $= A * R / 1000$ m <sup>3</sup> )                                                               |
| L                      |                    | Minimum length for side of square pit [ $= -O/L + (O/L^2 + 4 * [Vol Pit / L^2] * Y)^{0.5} / (2 * [Vol Pit / L^2])$ ]       |
| A <sub>500</sub>       |                    | Internal surface area of soakaway to 50% effective depth; excl. base area                                                  |
| A <sub>500</sub> / L   | 2.20               |                                                                                                                            |
| O                      |                    | Outflow from soakaway ( $= A_{500} * f * D$ m <sup>3</sup> )                                                               |
| Vol Pit                |                    | Effective storage volume of whole pit (ignoring the rings)                                                                 |
| Vol Pit/L <sup>2</sup> | 0.33               |                                                                                                                            |
| X                      | 0.78               | $= (VolR1 + VolR2) - (VoidR1 + VoidR2)$                                                                                    |
| Y                      |                    | Inflow (I) minus value X                                                                                                   |

| D       | Z1   | M5-D  | Inflow | R=M10-D | I=A*R | O / L  | Y     | L (m) |
|---------|------|-------|--------|---------|-------|--------|-------|-------|
| minutes |      | mm    | Z2     | mm      |       |        |       |       |
| 5       | 0.33 | 6.60  | 1.19   | 7.85    | 3.93  | 0.0290 | 3.15  | 3.05  |
| 10      | 0.48 | 9.60  | 1.22   | 11.71   | 5.86  | 0.0579 | 5.08  | 3.84  |
| 15      | 0.58 | 11.60 | 1.24   | 14.38   | 7.19  | 0.0869 | 6.41  | 4.28  |
| 30      | 0.76 | 15.20 | 1.24   | 18.85   | 9.42  | 0.1738 | 8.65  | 4.86  |
| 60      | 1.00 | 20.00 | 1.24   | 24.80   | 12.40 | 0.3477 | 11.62 | 5.43  |
| 120     | 1.27 | 25.40 | 1.22   | 30.99   | 15.49 | 0.6954 | 14.72 | 5.71  |
| 240     | 1.64 | 32.80 | 1.19   | 39.03   | 19.52 | 1.3908 | 18.74 | 5.72  |
| 260     | 1.88 | 37.60 | 1.17   | 43.99   | 22.00 | 1.5066 | 21.22 | 6.05  |
| 600     | 2.24 | 44.80 | 1.14   | 51.07   | 25.54 | 3.4769 | 24.76 | 4.87  |
| 1440    | 3.10 | 62.00 | 1.13   | 70.06   | 35.03 | 8.3445 | 34.25 | 3.59  |

**For square pit:**

Critical Length L = 6.05 m  
Time to Empty 50% = 3.06 hrs

**Consider rectangular alternative:**

Perimeter P = 4\*L = 2\*A + 2\*B

Adopt A = 6.05 1.20 3.00 m  
Then B = 6.05 10.91 9.11 m

Job No: Test  
Project: Based on BRE Digest 365 Worked Example page 7

Date: 06/01/09  
By: DA

**SOAKAWAY DESIGN TO BRE 365**

|                        |                   |                                                                                                                                   |
|------------------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------|
| A                      | 95 m <sup>2</sup> | Impermeable Surface Area of Catchment                                                                                             |
| f                      | 3.30E-05 m/sec    | Infiltration rate f of soil into which soakaway drains                                                                            |
| d                      | 1.5 m             | Effective storage depth of soakaway                                                                                               |
| VR                     | 0.3               | Free volume (void) ratio of fill to pit around rings                                                                              |
| Twall                  | 0.07 m            | Wall Thickness of rings                                                                                                           |
| D1                     | 0.9 m             | Internal diameter of Ring 1                                                                                                       |
| Vol R1                 | 0.95              | Storage capacity of ring 1 ( $= 3.142 \cdot (D1^2 \cdot 0.5)^2 \cdot d \cdot m^3$ )                                               |
| Void R1                | 0.382             | Equivalent volume of Ring 1 (incl wall) at void ratio of outer fill ( $= 3.142 \cdot (D1 + Twall)^2 \cdot d \cdot VR \cdot m^3$ ) |
| D2                     | 0 m               | Internal diameter of Ring 2                                                                                                       |
| Vol R2                 | 0.00              | Storage capacity of ring 2 ( $= 3.142 \cdot (D2^2 \cdot 0.5)^2 \cdot d \cdot m^3$ )                                               |
| Void R2                | 0.000             | Equivalent volume of Ring 2 (incl wall) at void ratio of outer fill ( $= 3.142 \cdot (D2 + Twall)^2 \cdot d \cdot VR \cdot m^3$ ) |
| M5-60 min              | 20 mm             | Base Rainfall                                                                                                                     |
| D                      |                   | Storm duration (in minutes)                                                                                                       |
| r                      | 0.35              | Rainfall ration (From BRE 365 Figure 1)                                                                                           |
| Z1                     |                   | Factor from BRE 365 Table 1 based on M5-D and 'r' from Fig 1                                                                      |
| M5-D                   |                   | Total rainfall in design storm duration D for 5-year return period ( $= Z1 \cdot D$ mm)                                           |
| Location               |                   | England and Wales                                                                                                                 |
| Z2                     |                   | Factor from BRE 365 Table 2 based on M5-D                                                                                         |
| M10-D                  |                   | Total rainfall in design storm duration D for 10 year return period ( $= M5-D \cdot Z2$ mm)                                       |
| R                      |                   | $= M10-D$                                                                                                                         |
| I                      |                   | Total inflow to soakaway ( $= A \cdot R / 1000$ m <sup>3</sup> )                                                                  |
| L                      |                   | Minimum length for side of square pit [ $= -O/L + (O/L^2 + 4 \cdot [Vol Pit/L^2] \cdot Y)^{0.5} / (2 \cdot [Vol Pit/L^2])$ ]      |
| A <sub>50</sub>        |                   | Internal surface area of soakaway to 50% effective depth, excl. base area                                                         |
| A <sub>50</sub> / L    | 3.00              |                                                                                                                                   |
| O                      |                   | Outflow from soakaway ( $= A_{50} \cdot T \cdot D$ m <sup>3</sup> )                                                               |
| Vol Pit                |                   | Effective storage volume of whole pit (ignoring the rings)                                                                        |
| Vol Pit/L <sup>2</sup> | 0.45              |                                                                                                                                   |
| X                      | 0.57              | $= (Vol R1 + Vol R2) - (Void R1 + Void R2)$                                                                                       |
| Y                      |                   | Inflow (I) minus value X                                                                                                          |

| D<br>minutes | Z1   | M5-D<br>mm | Inflow<br>Z2 | R=M10-D<br>mm | I=A*R | O/L    | Y    | L(m) |
|--------------|------|------------|--------------|---------------|-------|--------|------|------|
| 5            | 0.34 | 6.80       | 1.19         | 8.09          | 0.77  | 0.0297 | 0.20 | 0.63 |
| 10           | 0.49 | 9.80       | 1.22         | 11.96         | 1.14  | 0.0594 | 0.56 | 1.06 |
| 15           | 0.59 | 11.80      | 1.24         | 14.63         | 1.39  | 0.0891 | 0.82 | 1.25 |
| 30           | 0.77 | 15.40      | 1.24         | 19.10         | 1.81  | 0.1782 | 1.24 | 1.48 |
| 60           | 1.00 | 20.00      | 1.24         | 24.80         | 2.36  | 0.3564 | 1.78 | 1.63 |
| 120          | 1.25 | 25.00      | 1.22         | 30.50         | 2.90  | 0.7128 | 2.33 | 1.62 |
| 240          | 1.57 | 31.40      | 1.19         | 37.37         | 3.55  | 1.4256 | 2.98 | 1.44 |
| 260          | 1.78 | 35.60      | 1.17         | 41.65         | 3.96  | 1.5444 | 3.38 | 1.52 |
| 600          | 2.12 | 42.40      | 1.14         | 48.34         | 4.59  | 3.5640 | 4.02 | 1.00 |
| 1440         | 2.84 | 56.80      | 1.13         | 64.16         | 6.10  | 8.5536 | 5.53 | 0.63 |

**For square pit:**

Critical Length L = 1.63 m  
Time to Empty 50% = 1.52 hrs

**Consider rectangular alternative:**

Perimeter P = 4\*L = 2\*A + 2\*B

Adopt A = 1.63      0.90      8.00 m  
Then B = 1.63      2.37      -4.73 m

## Appendix D Access Road Soakaways and Catch-pits

| Project                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                  |             |       | TRAFFIC AND TRANSPORT PLANNING                                                                                                                                                                                                                                                                                                                                                                                             |                       |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-------------|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| MORSPAN HOLDINGS LTD<br>PROPOSED ACCESS ROAD AT<br>LLANELLEN COURT, LLANELLEN<br>ABERGAVENNY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                  |             |       |                                                                                                                                                                                                                                                                                                                                                                                                                            |                       |
| Element                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | PROPOSED ACCESS<br>ROAD DRAINAGE | Project No. | C2155 | Sheet No.<br>1 of 8                                                                                                                                                                                                                                                                                                                                                                                                        | Rev.                  |
| Ref.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Calculations                     |             |       | Output                                                                                                                                                                                                                                                                                                                                                                                                                     |                       |
| <p><u>SOAKAWAY DESIGN</u></p> <p>Spreadsheet used in design based on BRE 365 method.</p> <p>Ref. Test spreadsheet based on design example page 7 (sheet 8/8)</p> <p><u>Soakaway SA2</u></p> <p>Area drained = <math>465 \text{ m}^2</math> (Ref Fig 2)</p> <p>Effective depth soakaway 1.1 m</p> <p><math>f = 4.39 \times 10^{-5}</math> (Trial Pit No 1)</p> <p>Dia soakaway chamber 1200 mm dia</p> <p>Wall thickness 70 mm</p> <p><math>r = 0.25</math></p> <p>From input, results of spreadsheet indicate a critical size soakaway = <math>5.77 \times 5.77 \text{ m}</math></p> <p>and time to empty 50% = 2.93 hrs</p> <p><u>Make soakaway pit 5.80 m sq.</u></p> <p>GL Approx 49.25 m</p> <p>Inlet IL 47.275 m</p> <p>Top Base 46.025 m</p> <p>Chamber dia 1200 mm</p> |                                  |             |       | <p><u>Input to Spreadsheet</u></p> <p><math>A = 465 \text{ m}^2</math></p> <p><math>d = 1.1 \text{ m}</math></p> <p><math>f = 4.39 \times 10^{-5}</math></p> <p><math>D1 = 1.2 \text{ m}</math></p> <p><math>T_{\text{wall}} = 0.07 \text{ m}</math></p> <p><math>r = 0.25</math></p> <p>&lt; 24 hrs<br/>BRE 365<br/>Size 5.8 m sq</p> <p>GL = 49.25 m</p> <p>Inlet 47.275 m</p> <p>Top Base 46.025 m</p> <p>Dia 1.2 m</p> |                       |
| Calculations                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                  | Revision    |       |                                                                                                                                                                                                                                                                                                                                                                                                                            |                       |
| By<br>DA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Date<br>15/4/17                  | By          | Date  | Checked                                                                                                                                                                                                                                                                                                                                                                                                                    | By<br>Date<br>Checked |

| Project                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                  |             |       | TRAFFIC AND TRANSPORT PLANNING                                                                                                                                                                                                                                                                                                                |      |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|
| MORSPAN HOLDINGS LTD<br>PROPOSED ACCESS ROAD AT<br>LLANELLEN COURT, LLANELLEN<br>ABERGAVENNY                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                  |             |       | Sheet No.                                                                                                                                                                                                                                                                                                                                     | Rev. |
| Element                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | PROPOSED ACCESS<br>ROAD DRAINAGE | Project No. | C2155 | 2 of 8                                                                                                                                                                                                                                                                                                                                        |      |
| Ref.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Calculations                     |             |       | Output                                                                                                                                                                                                                                                                                                                                        |      |
| <u>Soakaway SA3</u><br>Area draining = Area 3 + Area 4<br>(Ref Fig 2) = $275 + 205 = 480\text{m}^2$<br>Effective depth soakaway 1.1m<br>$f = 4.707 \times 10^{-5}$ (Trial Pit W02)<br>Chamber dia 1200 mm<br>Wall thickness 70 mm<br>$r = 0.25$<br><br>From results of spreadsheet critical<br>size soakaway = 5.78m<br>Time to empty 50% = 2.74 hrs<br><br><u>Make soakaway 5.80m sq.</u><br>GL Approx 50.05m<br>Inlet IL 47.97m<br>Top Base 46.72m<br>chamber dia 1200mm<br><br><u>Soakaway SA4</u><br>Area draining = $406\text{m}^2$<br>remainder of input to spreadsheet same<br>as for SA3<br><br>From results of spreadsheet critical<br>size soakaway = 5.15m sq.<br>Time to empty 50% = 2.48hrs |                                  |             |       | <u>Input to Spreadsheet</u><br>$A = 480\text{m}^2$<br>$d = 1.1\text{m}$<br>$f = 4.707 \times 10^{-5}$<br>$D1 = 1.2\text{m}$<br>$T_{\text{wall}} = 0.07\text{m}$<br>$r = 0.25$<br><br>< 24km BRE365<br>Size 5.8m sq.<br>GL 50.05m<br>Inlet 47.97<br>T/Base 46.72m<br>dia 1.20m<br><br><u>Input</u><br>$A = 406\text{m}^2$<br><br>< 24km BRE365 |      |
| Calculations                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                  | Revision    |       |                                                                                                                                                                                                                                                                                                                                               |      |
| By                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Date                             | By          | Date  | Checked                                                                                                                                                                                                                                                                                                                                       |      |
| DA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 15/4/17                          |             |       |                                                                                                                                                                                                                                                                                                                                               |      |

|                                                                                                                                                |                                  |             |       |                                                                                             |        |      |         |
|------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|-------------|-------|---------------------------------------------------------------------------------------------|--------|------|---------|
| <b>Project</b> MURSPAN HOLDINGS LTD<br>PROPOSED ACCESS ROAD AT<br>LLANELLEN COURT, LLANELLEN<br>ABERGAVENNY                                    |                                  |             |       | <b>TRAFFIC<br/>AND<br/>TRANSPORT<br/>PLANNING</b>                                           |        |      |         |
| Element                                                                                                                                        | PROPOSED ACCESS<br>ROAD DRAINAGE | Project No. | C2155 | Sheet No.                                                                                   | 3 of 8 | Rev. |         |
| Ref.                                                                                                                                           | Calculations                     |             |       | Output                                                                                      |        |      |         |
| Soakaway SA4 cont'd<br><u>Make soakaway 5.20 m sq.</u><br><br>GL Approx 50.25 m<br>Inlet IL 48.75 m<br>Top Base 47.50 m<br>Chamber dia 1200 mm |                                  |             |       | <u>Size 5.20 m sq</u><br><br>GL = 50.25 m<br>Inlet 48.75 m<br>Top base 47.50 m<br>Dia 1.2 m |        |      |         |
| Calculations                                                                                                                                   |                                  | Revision    |       |                                                                                             |        |      |         |
| By                                                                                                                                             | Date                             | By          | Date  | Checked                                                                                     | By     | Date | Checked |
| DS                                                                                                                                             | 15/4/17                          |             |       |                                                                                             |        |      |         |



5/8

Job No C2155  
Project Llanellen Court Access Road SOAKAWAY SA2

Date 13/04/17  
By DA

**SOAKAWAY DESIGN TO BRE 365**

|                        |                    |                                                                                                                            |
|------------------------|--------------------|----------------------------------------------------------------------------------------------------------------------------|
| A                      | 465 m <sup>2</sup> | Impermeable Surface Area of Catchment                                                                                      |
| f                      | 4.39E-05 m/sec     | Infiltration rate f of soil into which soakaway drains                                                                     |
| d                      | 1.1 m              | Effective storage depth of soakaway                                                                                        |
| VR                     | 0.3                | Free volume (void) ratio of fill to pit around rings                                                                       |
| Twall                  | 0.07 m             | Wall Thickness of rings                                                                                                    |
| D1                     | 1.2 m              | Internal diameter of Ring 1                                                                                                |
| Vol R1                 | 1.24               | Storage capacity of ring 1 ( $= 3.142 * (D1^2 * 0.5)^2 * d$ m <sup>3</sup> )                                               |
| Void R1                | 0.465              | Equivalent volume of Ring 1 (incl wall) at void ratio of outer fill ( $= 3.142 * (D1 + Twall)^2 * d * VR$ m <sup>3</sup> ) |
| D2                     | 0 m                | Internal diameter of Ring 2                                                                                                |
| Vol R2                 | 0.00               | Storage capacity of ring 2 ( $= 3.142 * (D2^2 * 0.5)^2 * d$ m <sup>3</sup> )                                               |
| Void R2                | 0.000              | Equivalent volume of Ring 2 (incl wall) at void ratio of outer fill ( $= 3.142 * (D2 + Twall)^2 * d * VR$ m <sup>3</sup> ) |
| M5-60 min              | 20 mm              | Base Rainfall                                                                                                              |
| D                      |                    | Storm duration (in minutes)                                                                                                |
| r                      | 0.25               | Rainfall ration (From BRE 365 Figure 1)                                                                                    |
| Z1                     |                    | Factor from BRE 365 Table 1 based on M5-D and 'r' from Fig 1                                                               |
| M5-D                   |                    | Total rainfall in design storm duration D for 5-year return period ( $= Z1 * D$ mm)                                        |
| Location               |                    | England and Wales                                                                                                          |
| Z2                     |                    | Factor from BRE 365 Table 2 based on M5-D                                                                                  |
| M10-D                  |                    | Total rainfall in design storm duration D for 10 year return period ( $= M5-D * Z2$ mm)                                    |
| R                      |                    | $= M10-D$                                                                                                                  |
| I                      |                    | Total inflow to soakaway ( $= A * R / 1000$ m <sup>3</sup> )                                                               |
| L                      |                    | Minimum length for side of square pit [ $= -O/L + (O/L^2 + 4 * [Vol Pit / L^2] * Y)^{0.5} / (2 * [Vol Pit / L^2])$ ]       |
| A <sub>500</sub>       |                    | Internal surface area of soakaway to 50% effective depth; excl. base area                                                  |
| A <sub>500</sub> / L   | 2.20               |                                                                                                                            |
| O                      |                    | Outflow from soakaway ( $= A_{500} * f * D$ m <sup>3</sup> )                                                               |
| Vol Pit                |                    | Effective storage volume of whole pit (ignoring the rings)                                                                 |
| Vol Pit/L <sup>2</sup> | 0.33               |                                                                                                                            |
| X                      | 0.78               | $= (Vol R1 + Vol R2) - (Void R1 + Void R2)$                                                                                |
| Y                      |                    | Inflow (I) minus value X                                                                                                   |

| D       | Z1   | M5-D  | Inflow | R=M10-D | I=A*R | O / L  | Y     | L (m) |
|---------|------|-------|--------|---------|-------|--------|-------|-------|
| minutes |      | mm    | Z2     | mm      |       |        |       |       |
| 5       | 0.33 | 6.60  | 1.19   | 7.85    | 3.65  | 0.0290 | 2.87  | 2.91  |
| 10      | 0.48 | 9.60  | 1.22   | 11.71   | 5.45  | 0.0579 | 4.67  | 3.67  |
| 15      | 0.58 | 11.60 | 1.24   | 14.38   | 6.69  | 0.0869 | 5.91  | 4.10  |
| 30      | 0.76 | 15.20 | 1.24   | 18.85   | 8.76  | 0.1738 | 7.99  | 4.66  |
| 60      | 1.00 | 20.00 | 1.24   | 24.80   | 11.53 | 0.3477 | 10.75 | 5.21  |
| 120     | 1.27 | 25.40 | 1.22   | 30.99   | 14.41 | 0.6954 | 13.63 | 5.46  |
| 240     | 1.64 | 32.80 | 1.19   | 39.03   | 18.15 | 1.3908 | 17.37 | 5.45  |
| 260     | 1.88 | 37.60 | 1.17   | 43.99   | 20.46 | 1.5066 | 19.68 | 5.77  |
| 600     | 2.24 | 44.80 | 1.14   | 51.07   | 23.75 | 3.4769 | 22.97 | 4.60  |
| 1440    | 3.10 | 62.00 | 1.13   | 70.06   | 32.58 | 8.3445 | 31.80 | 3.36  |

**For square pit:**

Critical Length L = 5.77 m  
Time to Empty 50% = 2.93 hrs

**Consider rectangular alternative:**

Perimeter P = 4\*L = 2\*A + 2\*B

Adopt A = 5.77 1.20  
Then B = 5.77 10.34

3.00 m  
8.54 m

6/8

|         |                                          |      |          |
|---------|------------------------------------------|------|----------|
| Job No  | C2155                                    | Date | 13/04/17 |
| Project | Llanellen Court Access Road SOAKAWAY SA3 | By   | DA       |

**SOAKAWAY DESIGN TO BRE 365**

|                        |                    |                                                                                                                                                     |
|------------------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| A                      | 480 m <sup>2</sup> | Impermeable Surface Area of Catchment                                                                                                               |
| f                      | 4.71E-05 m/sec     | Infiltration rate f of soil into which soakaway drains                                                                                              |
| d                      | 1.1 m              | Effective storage depth of soakaway                                                                                                                 |
| VR                     | 0.3                | Free volume (void) ratio of fill to pit around rings                                                                                                |
| Twall                  | 0.07 m             | Wall Thickness of rings                                                                                                                             |
| D1                     | 1.2 m              | Internal diameter of Ring 1                                                                                                                         |
| Vol R1                 | 1.24               | Storage capacity of ring 1 (= 3.142 * (D1*0.5) <sup>2</sup> * d m <sup>3</sup> )                                                                    |
| Void R1                | 0.465              | Equivalent volume of Ring 1 (incl wall) at void ratio of outer fill (= 3.142*(D1+Twall) <sup>2</sup> *d*VR m <sup>3</sup> )                         |
| D2                     | 0 m                | Internal diameter of Ring 2                                                                                                                         |
| Vol R2                 | 0.00               | Storage capacity of ring 2 (= 3.142 * (D2*0.5) <sup>2</sup> * d m <sup>3</sup> )                                                                    |
| Void R2                | 0.000              | Equivalent volume of Ring 2 (incl wall) at void ratio of outer fill (= 3.142*(D2+Twall) <sup>2</sup> *d*VR m <sup>3</sup> )                         |
| M5-60 min              | 20 mm              | Base Rainfall                                                                                                                                       |
| D                      |                    | Storm duration (in minutes)                                                                                                                         |
| r                      | 0.25               | Rainfall ration (From BRE 365 Figure 1)                                                                                                             |
| Z1                     |                    | Factor from BRE 365 Table 1 based on M5-D and 'r' from Fig 1                                                                                        |
| M5-D                   |                    | Total rainfall in design storm duration D for 5-year return period (=Z1*D mm)                                                                       |
| Location               |                    | England and Wales                                                                                                                                   |
| Z2                     |                    | Factor from BRE 365 Table 2 based on M5-D                                                                                                           |
| M10-D                  |                    | Total rainfall in design storm duration D for 10 year return period (=M5-D*Z2 mm)                                                                   |
| R                      |                    | =M10-D                                                                                                                                              |
| I                      |                    | Total inflow to soakaway (=A*R/1000 m <sup>3</sup> )                                                                                                |
| L                      |                    | Minimum length for side of square pit [= -O/L + (O/L <sup>2</sup> +4*[Vol Pit/L <sup>2</sup> ]*Y) <sup>0.5</sup> / (2 * [Vol Pit/L <sup>2</sup> ])] |
| A <sub>50</sub>        |                    | Internal surface area of soakaway to 50% effective depth; excl. base area                                                                           |
| A <sub>50</sub> / L    | 2.20               |                                                                                                                                                     |
| O                      |                    | Outflow from soakaway (=A <sub>50</sub> *f*D m <sup>3</sup> )                                                                                       |
| Vol Pit                |                    | Effective storage volume of whole pit (ignoring the rings)                                                                                          |
| Vol Pit/L <sup>2</sup> | 0.33               |                                                                                                                                                     |
| X                      | 0.78               | = (VolR1+VolR2)-(VoidR1+VoidR2)                                                                                                                     |
| Y                      |                    | Inflow (I) minus value X                                                                                                                            |

| D       | Z1   | M5-D  | Inflow | R=M10-D | I=A*R | O / L  | Y     | L (m) |
|---------|------|-------|--------|---------|-------|--------|-------|-------|
| minutes |      | mm    | Z2     | mm      |       |        |       |       |
| 5       | 0.33 | 6.60  | 1.19   | 7.85    | 3.77  | 0.0311 | 2.99  | 2.96  |
| 10      | 0.48 | 9.60  | 1.22   | 11.71   | 5.62  | 0.0621 | 4.84  | 3.74  |
| 15      | 0.58 | 11.60 | 1.24   | 14.38   | 6.90  | 0.0932 | 6.13  | 4.17  |
| 30      | 0.76 | 15.20 | 1.24   | 18.85   | 9.05  | 0.1864 | 8.27  | 4.73  |
| 60      | 1.00 | 20.00 | 1.24   | 24.80   | 11.90 | 0.3728 | 11.13 | 5.27  |
| 120     | 1.27 | 25.40 | 1.22   | 30.99   | 14.87 | 0.7456 | 14.10 | 5.50  |
| 240     | 1.64 | 32.80 | 1.19   | 39.03   | 18.74 | 1.4912 | 17.96 | 5.46  |
| 260     | 1.88 | 37.60 | 1.17   | 43.99   | 21.12 | 1.6154 | 20.34 | 5.78  |
| 600     | 2.24 | 44.80 | 1.14   | 51.07   | 24.51 | 3.7279 | 23.74 | 4.54  |
| 1440    | 3.10 | 62.00 | 1.13   | 70.06   | 33.63 | 8.9471 | 32.85 | 3.28  |

**For square pit:**

Critical Length L = 5.78 m  
Time to Empty 50% = 2.74 hrs

**Consider rectangular alternative:**

Perimeter P = 4\*L = 2\*A + 2\*B

Adopt A = 5.78 1.20  
Then B = 5.78 10.35

3.00 m  
8.55 m

SA 3.xls - 14/04/17

7/8

Job No C2155  
 Project Llanellen Court Access Road SOAKAWAY SA4

Date 13/04/17  
 By DA

**SOAKAWAY DESIGN TO BRE 365**

|                        |                    |                                                                                                                                                     |
|------------------------|--------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| A                      | 406 m <sup>2</sup> | Impermeable Surface Area of Catchment                                                                                                               |
| f                      | 4.71E-05 m/sec     | Infiltration rate f of soil into which soakaway drains                                                                                              |
| d                      | 1.1 m              | Effective storage depth of soakaway                                                                                                                 |
| VR                     | 0.3                | Free volume (void) ratio of fill to pit around rings                                                                                                |
| Twall                  | 0.07 m             | Wall Thickness of rings                                                                                                                             |
| D1                     | 1.2 m              | Internal diameter of Ring 1                                                                                                                         |
| Vol R1                 | 1.24               | Storage capacity of ring 1 (= 3.142 * (D1*0.5) <sup>2</sup> * d m <sup>3</sup> )                                                                    |
| Void R1                | 0.465              | Equivalent volume of Ring 1 (incl wall) at void ratio of outer fill (= 3.142*(D1+Twall) <sup>2</sup> *d*VR m <sup>3</sup> )                         |
| D2                     | 0 m                | Internal diameter of Ring 2                                                                                                                         |
| Vol R2                 | 0.00               | Storage capacity of ring 2 (= 3.142 * (D2*0.5) <sup>2</sup> * d m <sup>3</sup> )                                                                    |
| Void R2                | 0.000              | Equivalent volume of Ring 2 (incl wall) at void ratio of outer fill (= 3.142*(D2+Twall) <sup>2</sup> *d*VR m <sup>3</sup> )                         |
| M5-60 min              | 20 mm              | Base Rainfall                                                                                                                                       |
| D                      |                    | Storm duration (in minutes)                                                                                                                         |
| r                      | 0.25               | Rainfall ration (From BRE 365 Figure 1)                                                                                                             |
| Z1                     |                    | Factor from BRE 365 Table 1 based on M5-D and 'r' from Fig 1                                                                                        |
| M5-D                   |                    | Total rainfall in design storm duration D for 5-year return period (=Z1*D mm)                                                                       |
| Location               |                    | England and Wales                                                                                                                                   |
| Z2                     |                    | Factor from BRE 365 Table 2 based on M5-D                                                                                                           |
| M10-D                  |                    | Total rainfall in design storm duration D for 10 year return period (=M5-D*Z2 mm)                                                                   |
| R                      |                    | =M10-D                                                                                                                                              |
| I                      |                    | Total inflow to soakaway (=A*R/1000 m <sup>3</sup> )                                                                                                |
| L                      |                    | Minimum length for side of square pit [= -O/L + (O/L <sup>2</sup> +4*[Vol Pit/L <sup>2</sup> ]*Y) <sup>0.5</sup> / (2 * [Vol Pit/L <sup>2</sup> ])] |
| A <sub>50</sub>        |                    | Internal surface area of soakaway to 50% effective depth; excl. base area                                                                           |
| A <sub>50</sub> / L    | 2.20               |                                                                                                                                                     |
| O                      |                    | Outflow from soakaway (=A <sub>50</sub> *f*D m <sup>3</sup> )                                                                                       |
| Vol Pit                |                    | Effective storage volume of whole pit (ignoring the rings)                                                                                          |
| Vol Pit/L <sup>2</sup> | 0.33               |                                                                                                                                                     |
| X                      | 0.78               | = (VolR1+VolR2)-(VoidR1+VoidR2)                                                                                                                     |
| Y                      |                    | Inflow (I) minus value X                                                                                                                            |

| D       | Z1   | M5-D  | Inflow | R=M10-D | I=A*R | O / L  | Y     | L (m) |
|---------|------|-------|--------|---------|-------|--------|-------|-------|
| minutes |      | mm    | Z2     | mm      |       |        |       |       |
| 5       | 0.33 | 6.60  | 1.19   | 7.85    | 3.19  | 0.0311 | 2.41  | 2.66  |
| 10      | 0.48 | 9.60  | 1.22   | 11.71   | 4.76  | 0.0621 | 3.98  | 3.38  |
| 15      | 0.58 | 11.60 | 1.24   | 14.38   | 5.84  | 0.0932 | 5.06  | 3.78  |
| 30      | 0.76 | 15.20 | 1.24   | 18.85   | 7.65  | 0.1864 | 6.87  | 4.29  |
| 60      | 1.00 | 20.00 | 1.24   | 24.80   | 10.07 | 0.3728 | 9.29  | 4.77  |
| 120     | 1.27 | 25.40 | 1.22   | 30.99   | 12.58 | 0.7456 | 11.80 | 4.96  |
| 240     | 1.64 | 32.80 | 1.19   | 39.03   | 15.85 | 1.4912 | 15.07 | 4.87  |
| 260     | 1.88 | 37.60 | 1.17   | 43.99   | 17.86 | 1.6154 | 17.08 | 5.15  |
| 600     | 2.24 | 44.80 | 1.14   | 51.07   | 20.74 | 3.7279 | 19.96 | 3.96  |
| 1440    | 3.10 | 62.00 | 1.13   | 70.06   | 28.44 | 8.9471 | 27.67 | 2.80  |

**For square pit:**

Critical Length L = 5.15 m  
 Time to Empty 50% = 2.48 hrs

**Consider rectangular alternative:**

Perimeter P = 4\*L = 2\*A + 2\*B

Adopt A = 5.15 1.20 3.00 m  
 Then B = 5.15 9.10 7.30 m

SA 4.xls - 14/04/17

Test 8/8  
Spreadsheet

Job No  
Project

Test  
Based on BRE Digest 365 Worked Example page 7

Date  
By

06/01/09  
DA

### SOAKAWAY DESIGN TO BRE 365

|                        |                   |                                                                                                                                                     |
|------------------------|-------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| A                      | 95 m <sup>2</sup> | Impermeable Surface Area of Catchment                                                                                                               |
| f                      | 3.30E-05 m/sec    | Infiltration rate f of soil into which soakaway drains                                                                                              |
| d                      | 1.5 m             | Effective storage depth of soakaway                                                                                                                 |
| VR                     | 0.3               | Free volume (void) ratio of fill to pit around rings                                                                                                |
| Twall                  | 0.07 m            | Wall Thickness of rings                                                                                                                             |
| D1                     | 0.9 m             | Internal diameter of Ring 1                                                                                                                         |
| Vol R1                 | 0.95              | Storage capacity of ring 1 (= 3.142 * (D1*0.5) <sup>2</sup> * d m <sup>3</sup> )                                                                    |
| Void R1                | 0.382             | Equivalent volume of Ring 1 (incl wall) at void ratio of outer fill (= 3.142*(D1+Twall) <sup>2</sup> *d*VR m <sup>3</sup> )                         |
| D2                     | 0 m               | Internal diameter of Ring 2                                                                                                                         |
| Vol R2                 | 0.00              | Storage capacity of ring 2 (= 3.142 * (D2*0.5) <sup>2</sup> * d m <sup>3</sup> )                                                                    |
| Void R2                | 0.000             | Equivalent volume of Ring 2 (incl wall) at void ratio of outer fill (= 3.142*(D2+Twall) <sup>2</sup> *d*VR m <sup>3</sup> )                         |
| M5-60 min              | 20 mm             | Base Rainfall                                                                                                                                       |
| D                      |                   | Storm duration (in minutes)                                                                                                                         |
| r                      | 0.35              | Rainfall ration (From BRE 365 Figure 1)                                                                                                             |
| Z1                     |                   | Factor from BRE 365 Table 1 based on M5-D and 'r' from Fig 1                                                                                        |
| M5-D                   |                   | Total rainfall in design storm duration D for 5-year return period (=Z1*D mm)                                                                       |
| Location               |                   | England and Wales                                                                                                                                   |
| Z2                     |                   | Factor from BRE 365 Table 2 based on M5-D                                                                                                           |
| M10-D                  |                   | Total rainfall in design storm duration D for 10 year return period (=M5-D*Z2 mm)                                                                   |
| R                      |                   | =M10-D                                                                                                                                              |
| I                      |                   | Total inflow to soakaway (=A*R/1000 m <sup>3</sup> )                                                                                                |
| L                      |                   | Minimum length for side of square pit [= -O/L + (O/L <sup>2</sup> +4*[Vol Pit/L <sup>2</sup> ]*Y) <sup>0.5</sup> / (2 * [Vol Pit/L <sup>2</sup> ])] |
| A <sub>50</sub>        |                   | Internal surface area of soakaway to 50% effective depth, excl. base area                                                                           |
| A <sub>50</sub> / L    | 3.00              |                                                                                                                                                     |
| O                      |                   | Outflow from soakaway (=A <sub>50</sub> *f m <sup>3</sup> )                                                                                         |
| Vol Pit                |                   | Effective storage volume of whole pit (ignoring the rings)                                                                                          |
| Vol Pit/L <sup>2</sup> | 0.45              |                                                                                                                                                     |
| X                      | 0.57              | = (Vol R1+Vol R2)-(Void R1+Void R2)                                                                                                                 |
| Y                      |                   | Inflow (I) minus value X                                                                                                                            |

| D       | Z1   | M5-D  | Inflow | Z2   | R=M10-D | I=A*R | O / L  | Y    | L (m) |
|---------|------|-------|--------|------|---------|-------|--------|------|-------|
| minutes |      | mm    |        |      | mm      |       |        |      |       |
| 5       | 0.34 | 6.80  | 1.19   | 1.22 | 8.09    | 0.77  | 0.0297 | 0.20 | 0.63  |
| 10      | 0.49 | 9.80  | 1.22   | 1.24 | 11.96   | 1.14  | 0.0594 | 0.56 | 1.06  |
| 15      | 0.59 | 11.80 | 1.24   | 1.24 | 14.63   | 1.39  | 0.0891 | 0.82 | 1.25  |
| 30      | 0.77 | 15.40 | 1.24   | 1.24 | 19.10   | 1.81  | 0.1762 | 1.24 | 1.48  |
| 60      | 1.00 | 20.00 | 1.24   | 1.22 | 24.60   | 2.36  | 0.3564 | 1.78 | 1.63  |
| 120     | 1.25 | 25.00 | 1.22   | 1.19 | 30.50   | 2.90  | 0.7128 | 2.33 | 1.82  |
| 240     | 1.57 | 31.40 | 1.17   | 1.17 | 37.37   | 3.55  | 1.4256 | 2.98 | 1.44  |
| 260     | 1.78 | 35.60 | 1.14   | 1.14 | 41.65   | 3.96  | 1.6444 | 3.38 | 1.52  |
| 500     | 2.12 | 42.40 | 1.13   | 1.13 | 48.34   | 4.59  | 3.5640 | 4.02 | 1.00  |
| 1440    | 2.84 | 56.80 | 1.13   | 1.13 | 64.18   | 6.10  | 8.5536 | 5.53 | 0.63  |

#### For square pit:

Critical Length L = 1.63 m  
Time to Empty 50% = 1.52 hrs

#### Consider rectangular alternative:

Perimeter P = 4\*L = 2\*A + 2\*B

Adopt A = 1.63 0.90 8.00 m  
Then B = 1.63 2.37 4.73 m

Soakaway design 2.xls - 15/04/17

## Appendix E Soakaway Detail

